

TECHNICAL DATASHEET



CleanAIR® Protective shield CA-3

Protective shield with replaceable acetate visor



Description

Protective shield with an easily replaceable acetate visor provides respiratory and face protection against splash of chemicals.

Application

CA-3 finds application in many sectors like environments with low chemical resistance requirements, chemical industry, laboratories and spray painting.



Techware Pty Ltd
ABN: 13 914 775 899
Phone: 1300 062 947
Email: sales@maxsafe.com.au
Website: www.maxsafe.com.au

Techware Pty Ltd
PO Box 4220
Hoppers Crossing
VIC 3029
Australia

DA-061_-_710301_-_Grinding_shield_CA-3_acetate_-_EN

© CleanAIR® All rights reserved

Revision: 2021_04_19
Output: 2021_04_19

TECHNICAL DATASHEET

CleanAIR® Protective shield CA-3

Protective shield with replaceable acetate visor



Technical specification

Product code	71 03 01		
Weight	520 g		
Dimensions	300 mm / 350 mm / 220 mm		
Visor dimensions	300 x 220 mm		
Colour	black		
Materials	Helmet shell - Polyamide Protective visor - Acetate		
Recommended hose type	71 00 60 - Light flexi hose (Female QuickLOCK™ - Internal thread CA40x1/7") Length: soft adjusting: 600 mm - 1 100 mm / Weight: 225 g		
Input (thread)	Airflow input thread - Male QuickLOCK™		
Standard	EN 12941	EN 14594	EN 166
Protection class / NPF*	TH2 / 50	2A / 50	FT
Storage conditions	- 10°C to + 55°C, humidity 20 - 95 % Rh		
Operating conditions	0°C to + 60°C, humidity 20 - 95 % Rh		

* depends on used PAPR unit / airline system

Disclaimer Notice

All the information contained herein is believed to be accurate and is subject to change without notice. Users should independently evaluate the suitability of each product for their own applications. CleanAIR® products are not designed for, and may not be used in, all applications.